


The **Straight Sided Insert (SI)** is a **threadless** check valve designed to be inserted into any cavity where a check valve is needed and threads are not desired. Consult the factory if your application requires tolerancing for a press fit installation. The SI valve can also be used as a low pressure relief valve or vacuum breaker by using the desired spring settings.




Nom. Pipe Size	Size Code	A	B	C	D	E ①	F	G	Orifice Diameter
1/2	D	0.656	0.56	0.16	0.718	0.53	0.01	0.031	0.348
3/4	F	0.780	0.59	0.16	0.900	0.61	0.00	0.063	0.464
1	H	1.000	0.69	0.19	1.125	0.78	0.11	0.063	0.593
1-1/4	I	1.312	0.81	0.19	1.500	0.85	0.09	0.063	0.890
1-1/2	J	1.625	0.88	0.25	1.781	1.01	0.15	0.063	1.135
2	K	1.875	0.88	0.25	2.187	1.19	0.70	0.063	1.385

① Maximum nominal dimension for a fully open valve with no spring.

Body Material ②	Availability	Non-Shock Pressure-Temp. Rating @ 100°F Consult factory for P-T rating above @ 100°F
316 Stainless Steel (SS)	Standard	3000 PSIG (1500 PSIG for o-ring seats)
Carbon Steel (CS)		
Brass (BR)		
Alloy 20 (A2)	Semi-standard	
Alloy C-276 (HC)		
MONEL® 400 or Alloy R405		
Alloy B (HB)	Contact the factory for these or other materials.	
Titanium (TI)		

② See page 56 for material grade information.

**Straight Sided Insert**  
For Water at 72°F



**Note:** All flow curves and Cv values presume the valves are fully open with 1/2 PSI cracking pressure springs. Consult the factory for more information.

STYLE SI C <sub>v</sub> VALUES & VALVE WEIGHTS		
C <sub>v</sub>	SIZE	ALL MATERIALS
2.4	1/2	0.6 oz.
4.2	3/4	1.0 oz.
6.6	1	1.7 oz.
11.0	1-1/4	3.3 oz.
17.4	1-1/2	5.3 oz.
32.0	2	8.2 oz.

See page 51 for Flow Formulae.  
Valve weights are approximate.

**HOW TO ORDER**  
**CHECK-ALL STYLE SI**

**BODY MATERIAL**

- ALLOY 20 = A2
- BRASS = BR
- CARBON STEEL = CS
- ALLOY B = HB
- ALLOY C-276 = HC
- MONEL® 400 OR ALLOY R405 = MO
- 316 SS = SS
- TITANIUM = TI

See p. 3 for temperature ratings

**SPRING CRACKING PRESSURES (PSI)** **Note:** Many other cracking pressures are available. All spring tolerances +/- 15%.

Must use decimal as a character unless selecting NO SPRING. Specify Exact Setting

SPRING RANGES	EXAMPLE
.000 TO .999	= .500
1.00 TO 9.99	= 1.50
10.0 TO 85.0	= 15.0
NO SPRING	= NOSPRG

**STANDARD CRACKING PRESSURES** ①

.125	.500	1.50	3.50
------	------	------	------


(Sizes D-J Only)

**SPECIAL OPTIONS**

T = FEP ENCAPSULATED SPRING

Contact the factory for more options

See p. 4 for temperature rating



Listed above are the most common material selections. Please contact the factory for additional options.

- ① .500 PSI is the only standard cracking pressure for spring materials other than Stainless Steel. .125 PSI springs are not recommended for installations with flow vertical down.
- ② Seat materials other than “metal-to-metal” have a maximum pressure rating of 1500 PSI. “Metal-to-Metal” and PTFE seats are not resilient. See page 52 for allowable leakage rates.
- ③ EP seats not recommended for use with Carbon Steel valves.